

Optional Accessories

For complete descriptions, dimensions, and part numbers of SunBriteTV accessories, please visit the Product Page at www.sunbriteTV.com.



Wall Mounts

Articulating Mounts provide smooth tilt, swivel and articulating action from 9" to 17" from the wall, and are available for all SunBriteTV models.

Tilt Mounts provide smooth tilt and are available for 32", 46" and 55" models.



Outdoor Dust Cover

This fitted outdoor dustcover is constructed with weatherproof 4-ply polypropylene UV protection fabric and velcro straps for a secure fit.

Outdoor Dust Covers are available for all models.



Patent Pending. All rights reserved. (C) 2010 SunBriteTV® LLC Revision 100106

Ceiling Mount

Provides tilt. Includes adjustable extension column and ceiling plate. Available for all models. SunbriteTV mounts include stainless steel hardware, and meet VESA standards.



Water-Resistant Universal Learning Remote Control

This remote control is water resistant, runs on long-life batteries, and is compatible with all SunBriteTV models.



Deck/Planter Pole

The pole and supporting flange are made from heavy-gauge aluminum or zinc-plated galvanized steel, and are powder-coated to eliminate corrosion issues.

The pole can be set in concrete, in a planter or bolted directly to a flat surface, such as a patio or pool deck.

Note: Mounting bracket is not included. Requires purchase of wall mount.

46" and 55" Deck/Planter Pole dimensions:
3"W x 3"D x 60"H

Mounting Flange is 12"W x 12"D

23" and 32" Deck/Planter Pole dimensions:
3"W x 3"D x 60"H

Mounting Flange is 8"W x 8"D



SunBriteTV RadioFM™

RadioFM is a wireless transmitter that sends audio from the SunBriteTV to your FM radio stereo system. RadioFM allows SunBriteTV's audio to be played through your spa's built-in speakers or any portable FM radio.

RadioFM is available for all models.

Designed for Permanent Residential and Commercial Outdoor Installations

Patio, Barbecue & Gazebo Areas • Poolside Cabanas
Restaurant Patios • Amusement Parks • Outdoor Venues



Model 5510HD is a 55" 1080p full-HD LCD with 120Hz frame rate.



Model 3220HD shown with detachable speaker module. Photo credit: poul.com



Model 4610HD is a 46" 1080p full-HD LCD shown without detachable speaker module.



All-Weather Outdoor LCD TV



SunBriteTV HD LCD TVs All-Weather Outdoor Feature-Set

- All-weather exterior protects internal components from rain, dirt, insects and scratches
- A contrast-enhancing, anti-reflective and scratch-resistant window protects the LCD screen
- Filtered airflow system keeps unit cool and dry in temperatures up to 122°F.
- Internal thermostatically-controlled heater protects TV in temperatures as low as -24° F.
- Watertight cable entry system with pass-through design keeps cables dry and allows for simplified connections.
- Water-resistant remote control



Models 5510HD

Shown with Detachable Speaker Module

LCD Screen:	55" diag. TFT
Resolution:	1920p x 1080p with 120 Hz Frame Rate
Contrast Ratio:	4000:1
Response Time:	4.5 milliseconds
HDMI Input:	x4
Dimensions:	52.46"W x 31.43"H (33.13"H without speaker module), x 7.80"D
Weight:	90.0 lbs., 95.0 lbs. with speaker module

Models 5510HD and 4610HD

Aspect Ratio:	16.9
Display Colors:	16.7 million
Input Power:	100-240 VAC, 50-60Hz 4.0 A MAX
Operating Temp.:	-24° to 122° F. (-31° to 50° C.)
Non-op. Temp.:	-24° to 140° F. (-31° to 60° C.) (Off-mode with power applied)
TV formats:	1080p, 1080i, 720p, 480p, 480i
Input:	Antenna/CATV (ATSC/QAM/NTSC) x1 Component YPbPr plus stereo audio x2 Composite video x 1, S-video x1 L/R audio x1 15-pin D-sub VGA plus Stereo Audio RS232 Serial
Audio:	TosLink, 5.1 Audio from DTV input only (TosLink Optical) x1
Speaker:	10-Watt x 2 channels, water-resistant detachable speaker module
Control Set:	RS232 serial Discrete IR control Concealed IR Window
Exterior:	Powder-coated aluminum
Warranty:	One-year, in-factory, parts and labor
Accessories Included:	Water-resistant remote control



Models 4610HD

Shown without Detachable Speaker Module

LCD Screen:	46" diag. TFT
Resolution:	1920p x 1080p
Contrast Ratio:	3500:1
Response Time:	6 milliseconds
HDMI Input:	x2
Dimensions:	44.72"W x 30.47"H (27.16"H without speaker module), x 6.85"D
Weight:	82.7 lbs., 86.8 lbs. with speaker module



Model 3220HD

Shown with Detachable Speaker Module

Speaker:	10-Watt x 2 channels, water-resistant detachable speaker module
Control Set:	RS232 serial Discrete IR control Concealed IR window
Exterior:	Powder-coated aluminum
Dimensions:	32.07"W x 23.20"H (20.02"H without speaker module), x 6.29"D
Weight:	37.5 lbs., 41.6 lbs. with speaker module

Models 3220HD and 3230HD

LCD Screen:	31.5" diag. TFT
Resolution:	1366 x 768
Aspect Ratio:	16.9
Contrast Ratio:	3000:1
Response Time:	8 milliseconds
Display Colors:	16.7 million
Input Power:	100-240 VAC, 50-60Hz 2.5A MAX
Operating Temp.:	-24° to 122° F. (-31° to 50° C.)
Non-op. Temp.:	-24° to 140° F. (-31° to 60° C.) (Off-mode with power applied)
TV formats:	1080i, 720p, 480i, 480p
Input:	Antenna/CATV, (ATSC/NTSC/QAM), HDMI x 2, S-Video x1 and composite video x1, L/R audio inputs x2 YCbCr/YPbPr and audio L/R channels x2 15-pin D-sub VGA plus stereo audio RS232 serial (Model 3220HD only)
Audio:	SPDIF audio output, analog headphone jack
Warranty:	One-year, in-factory, parts and labor
Accessories Included:	Water-resistant remote control with lithium battery; Removable table-top stand



Model 3230HD

Speakers:	10-Watt x 2 channels, water-resistant built-in speakers
Exterior:	Outdoor-rated ASA plastic resin
Dimensions:	32.21"W x 23.21"H x 6.97"D
Weight:	39 lbs.

LCD Screen:	23" diag. TFT
Resolution:	1366 x 768
Aspect Ratio:	16.9
Contrast Ratio:	700:1
Response Time:	8 milliseconds
Display Colors:	16.7 million
Input Power:	100-240 VAC, 50-60Hz 2.2 A Max
Operating Temp.:	-24° to 122° F. (-31° to 50° C.)
Non-op. Temp.:	-24° to 140° F. (-31° to 60° C.) (Off-mode with power applied)
TV formats:	1080i, 720p, 480p, 480i
Input:	Antenna/CATV, (ATSC/QAM/NTSC), HDMI x 2 S-Video x1 and composite video x1, L/R Audio inputs x2 YCbCr/YPbPr and audio L/R channels x2 15-pin D-sub VGA plus stereo audio RS232 serial*
Audio:	SPDIF Audio output, analog headphone jack
Speakers:	5-Watt x 2 channels, water-resistant built-in speakers
Dimensions:	23.51"W x 16.27"H x 4.9"D
Weight:	22 lbs.



Model 2310HD

Control Set:	RS232 serial* Discrete IR control*
Exterior:	Powder-coated aluminum
Warranty:	One-year, in-factory, parts and labor
Accessories Included:	Water-resistant remote control with lithium battery, Removable table-top stand

**Available only with Model 2310HD-Pro*